

Field Tile Sizes



Clay - CLA
CRDANTCLA848 - 8"x48" Matte



Walnut - WAL
CRDANTWAL848 - 8"x48" Matte



Wenge - WEN
CRDANTWEN848 - 8"x48" Matte



Clay - CLA
CRDANTCLA2424 - 24"x24" Matte



Walnut - WAL
CRDANTWAL2424 - 24"x24" Matte



Wenge - WEN
CRDANTWEN2424 - 24"x24" Matte



Photo Features 8"x48" Field Tile - Matte in Clay.



Antique

Glazed Color Body Porcelain

Photo Features 8"x48" Field Tile - Matte & 24"x24" Field Tile - Matte in Walnut.


SIZING & PACKAGING

Type	Shape	Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		CRDANT***848	8"x48"	Field Tile - Matte	4	10.12
		CRDANT***2424	24"x24"	Field Tile - Matte	3	11.63

ANSI TECHNICAL SPECIFICATIONS


	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	Pass ≤ 175 (ISO)	Unaffected	N/A	Pass (1,300 ISO)	≤ 0.5%	Unaffected

Shade Variation




APPLICATIONS

	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	● †	■	■	● †	■	■
Commercial	● †	■	■	● †	■	■



LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors
- ∅ Applications & ANSI Technical Specifications do not apply
- * Special Order only



† The TCNA does not rate products for exterior floors. Project specifier must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable.

Minimum grout joint must be 3/16 inch. Please refer to the most current TCNA Handbook for installation guidelines. It is recommended to install 24"x24" deco tiles in a diamond pattern without an offset. This tile must be installed with a straight set in the diamond pattern for the lines to match up. Please reference images on website.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

