Bedrosians[®] Tile & Stone

Chateau

Glazed Color Body Porcelain (4"x8" Glazed Ceramic Wall Tile)

Field Tile Sizes



Canvas - CAN
DOLCHACAN1224 - 12"x24" Honed
DOLCHACAN2424 - 24"x24" Honed



Smoke - SMO DOLCHASMO1224 - 12"x24" Honed DOLCHASMO2424 - 24"x24" Honed



Tobacco - TOB
DOLCHATOB1224 - 12"x24" Honed
DOLCHATOB2424 - 24"x24" Honed



Ocean - OCE
DOLCHAOCE1224 - 12"x24" Honed
DOLCHAOCE2424 - 24"x24" Honed



Midnight - MID DOLCHAMID1224 - 12"x24" Honed DOLCHAMID2424 - 24"x24" Honed

4"x8" Non-Rectified Glazed Ceramic Wall Tile - Honed



Canvas - CAN DOLCHACAN48



Smoke - SMO DOLCHASMO48



Tobacco - TOB



Ocean - OCE



Midnight - MID DOLCHAMID48

2"x2" Mosaic - Honed (12"x12" Sheet)




Canvas - CAN DOLCHACAN22MO



Smoke - SMO DOLCHASMO22MO



Tobacco - TOB DOLCHATOB22MO



Ocean - OCE DOLCHAOCE22MO



Midnight - MID DOLCHAMID22MO

Deco Patterns - Honed



DOLCHADIA1212CASM 12"x12" Diamond Deco Canvas, Smoke & Midnight



DOLCHAFIO1212CAOC 12"x12" Fiore Deco Canvas & Ocean



DOLCHAFIO1212CASM 12"x12" Fiore Deco Canvas & Smoke



DOLCHAFIO1212MICA 12"x12" Fiore Deco Canvas & Midnight



SIZING & PACKAGING

Туре	Shape		Item Code	Size	Description	Pcs / Ctn	Sf / Ctn
Field		Ø	DOLCHA···48	4"x8"	Non-Rectified Glazed Ceramic Wall Tile - Honed	32	6.89
			DOLCHA···1224	12"x24"	Field Tile - Honed	8	15.75
			DOLCHA···2424	24"x24"	Field Tile - Honed	4	15.83
Decos			DOLCHADIA1212CASM	12"x12"	Diamond Deco - Canvas, Smoke & Midnight - Honed	10	-
			DOLCHAFIO1212MICA	12"x12"	Fiore Deco - Canvas and Midnight - Honed	10	-
			DOLCHAFIO1212CAOC	12"x12"	Fiore Deco - Canvas and Ocean - Honed	10	-
			DOLCHAFIO1212CASM	12"x12"	Fiore Deco - Canvas and Smoke - Honed	10	-
Trim			DOLCHA•••312BN	3"x12"	Bullnose - Honed	15	-
		Ø	DOLCHA···48BN	4"x8"	Non-Rectified Glazed Ceramic Bullnose - Honed	12	-
Mosaic		Ø	DOLCHA····22MO	12"x12" Sheet	2"x2" Mosaic - Honed	-	-

ANSI TECHNICAL SPECIFICATIONS

	DCOF Acutest	PEI Rating ASTM# C1027	Frost Resistant ASTM# C1026	Scratch Resistance MOHS	Breaking Strength ASTM# C648	Water Absorption ASTM# C373	Chemical Resistance ASTM# C650
Results	≥ 0.42	4	Unaffected	7	≥ 350 lbf	≤ 0.5%	Unaffected






V3-Moderate

APPLICATIONS


	Floors	Walls	Countertops	Shower Floors	Shower Walls	Pools/Spas
Residential	•	•	•	•	•	•
Commercial	•	•	•	•	•	•



LEGEND

- Product rated for Interior & Exterior use
- Product rated for Interior use only
- † May be suitable for Exterior Floors

- Applications & ANSI Technical Specifications do not apply
- * Special Order only






























Minimum grout joint must be 3/16 inch. Please refer to the most current TCNA Handbook for installation guidelines. The TCNA does not rate products for exterior floors. Project specific must determine product suitability for exterior floor applications by evaluating specific project conditions, type of use, traffic, drainage, expected contaminants (such as water, oil, grease, etc.), wear, maintenance, and manufacturer's specifications and guidelines. Use caution--product may not be suitable for pool decks. Not suitable for ramps. No polished tiles; only textured surfaces may be suitable. It is recommended to install deco tiles without an offset.

Merchandising materials and samples are for general reference only and representative of a product's potential characteristics. Tile is subject to variation in color/shade, size, texture, and finish. Field, mosaic and trim tile may not match exactly. Blend tiles from different boxes to achieve consistent shade distribution. Installer and end user must conduct a dry mock layout under proper lighting conditions to inspect the product. Installation constitutes product acceptance. Improper installation, application, use, care and maintenance voids warranty. Reference the TCNA Handbook and ANSI for installation guidance. Please visit bedrosians.com for current product information. We reserve the right to make product changes at any time without notice.

