

# RAW PORCELAIN

—  
All the beauty of traditional plaster in a durable, unique porcelain.  
Stocked as a 24" × 24" tile in four matte neutral tones.



PICTURED: RAW GREY



# RAW PORCELAIN



*White<sup>6</sup>  
Matte*



*Linen  
Matte*



*Grey  
Matte*



*Black  
Matte*

APPLICATIONS								ATTRIBUTES		VARIATION		TAILORED TO CUSTOMIZATION <sup>3</sup>	
INTERIOR FLOOR	INTERIOR WALL	SHOWER WALL	SHOWER FLOOR	EXTERIOR FLOOR	EXTERIOR WALL	POOL/ FOUNTAIN	COUNTER TOP	DCOF <sup>2</sup>				CARPET CUTTING FIELD FINISH MOSAIC SADDLE VANITY TOP WATERJET	
Heavy Traffic Commercial	All	Yes, including steam	Yes <sup>1</sup>	Yes	Yes	No	Yes	0.62	0.62	0.64			
INSTALLATION/MAINTENANCE										RECTIFIED FIELD TILE			
SETTING MATERIAL	GROUT	GROUT JOINT	MEMBRANE	CAULK	SEALER	CLEANER	INSTALLATION INSTRUCTIONS	LAYOUT	DRY LAYOUT				
Ardex X77 White <sup>4</sup>	Ardex FL Rapid Set Sanded <sup>5</sup>	1/8" minimum	Mapei Mapelastick AquaDefense	Mapei Keracaulk Sanded	AquaMix Grout Release	AquaMix Concentrated Stone & Tile Cleaner	TCNA Handbook	33% max. offset	Recommended	23 5/8" x 23 5/8" x 3/8" Matte			
NOTES													
<sup>1</sup> Mosaic formats only <sup>2</sup> The standard requires a minimum wet DCOF Acutest value greater than 0.42 for ceramic tiles (inclusive of porcelain) for level interior spaces expected to be walked upon when wet. <sup>3</sup> Mosaic - Smallest mosaic size 3 x 3 <sup>4</sup> Alternate mortar - Ardex X5 White or Mapei Ultraflex LFT White <sup>5</sup> Alternate grout - Mapei Flexcolor CQ or Mapei Ultracolor Plus Sanded 7.5% Recycled Content <sup>6</sup> Light colored porcelains that meet the DCOF standard may have a more abrasive surface that might show dirt or debris. Remove with soap, water and firm scrubbing in order to clean. Consider this in the selection process.													