TERRE PORCELAIN

Presenting Terre, a large-format porcelain collection in warm earth tones, featuring a Ribbed finish with a slight undulating surface or a refined Raked finish. Sand is stocked in both Ribbed and Raked finishes, and Brick is exclusively stocked in Raked. Each tile is 24”x 48”.

TERRE PORCELAIN

Brick - Raked

Sand - Ribbed

Sand - Raked

APPLICATIONS

INTERIOR FLOOR	INTERIOR WALL	SHOWER WALL	SHOWER FLOOR	EXTERIOR FLOOR	EXTERIOR WALL	POOL/ FOUNTAIN	COUNTER TOP	FIREPLACE SURROUND
Commercial Heavy [1]	All	Yes, including steam	Yes, including steam [1]	Yes [1]	Yes, including freeze thaw	Yes [1]	Yes [1]	Yes

ATTRIBUTES

DCOF
0.57. 0.56. 0.57.

VARIATION



TAILORED TO CUSTOMIZATION

- CARPET CUTTING
- FIELD
- FINISH
- MOSAIC
- SADDLE
- VANITY TOP
- WATERJET

INSTALLATION/MAINTENANCE

SETTING MATERIAL	GROUT	GROUT JOINT	MEMBRANE	CAULK	SEALER	CLEANER	INSTALLATION INSTRUCTIONS	LAYOUT	DRY LAYOUT	QR LINK
Ardex X77 White Microtec Fiber Reinforced Mortar [2]	Ardex FL Rapid Set Sanded [3]	1/16" minimum	Ardex 8+9	Ardex SX	AquaMix Grout Release	AquaMix Concentrated Cleaner	TCNA Handbook	Max. 33% Offset	Recommended	

AVAILABLE SIZES

PORCELAIN RECTIFIED FIELD TILE
24" × 48" × 3/8"

NOTES

[1] Ribbed Sand is not approved for interior floors, shower floors, exterior floors, pools/fountains or countertops

[2] Alternate Setting Material - Ardex X5 White Medium Bed Mortar or Mapei Ultraflex LFT White

[3] Alternate Grout - Ardex DG 1 – One Component Grout or Mapei Ultracolor Plus FA

Tech Note: Showers: Product MUST be installed in accordance with current TCNA Handbook tile methods. Dry laying of this product prior to installation is recommended. Porcelains that meet the DCOF standard may have a more abrasive surface that might show dirt or debris. Remove with soap, water and firm scrubbing in order to clean. Consider this in the selection process. Per TCNA guidelines, running bond/brick joint patterns to be set with a max. offset of 33% and min. grout joint of 1/16", unless otherwise approved by the key decision maker. Grout release can be utilized, and bag grouting may be considered.