# RAW PORCELAIN

All the beauty of traditional plaster in a durable, unique porcelain.
Stocked as a 24” x 24”” tile in three matte neutral tones.

# RAW PORCELAIN

*White*
*Matte*

*Linen*
*Matte*

*Grey*
*Matte*

## APPLICATIONS

| INTERIOR FLOOR | INTERIOR WALL | SHOWER WALL | SHOWER FLOOR | EXTERIOR FLOOR | EXTERIOR WALL | POOL/ FOUNTAIN | COUNTER TOP |
|---|---|---|---|---|---|---|---|
| Heavy Traffic Commercial | All | Yes, including steam | Yes [1] | Yes | Yes | No | Yes |

## ATTRIBUTES

| DCOF [2] |
|---|
| 0.62<br>0.62<br>0.64 |

## VARIATION




## TAILORED TO CUSTOMIZATION [3]

- CARPET CUTTING
- **FIELD**
- FINISH
- **MOSAIC**
- SADDLE
- VANITY TOP
- WATERJET

## INSTALLATION/MAINTENANCE

| SETTING MATERIAL | GROUT | GROUT JOINT | MEMBRANE | CAULK | SEALER | CLEANER | INSTALLATION INSTRUCTIONS | LAYOUT | DRY LAYOUT |
|---|---|---|---|---|---|---|---|---|---|
| Ardex X77 White [4] | Ardex FL Rapid Set Sanded [5] | 1/8" minimum | Mapei Mapelastic AquaDefense | Mapei Keracaulk Sanded | AquaMix Grout Release | AquaMix Concentrated Stone & Tile Cleaner | TCNA Handbook | 33% max. offset | Recommended |

## RECTIFIED FIELD TILE



23 5/8" x 23 5/8" x 3/8"
Matte

## NOTES

[1] Mosaic formats only
[2] The standard requires a minimum wet DCOF Acutest value greater than 0.42 for ceramic tiles (inclusive of porcelain) for level interior spaces expected to be walked upon when wet. Whiter porcelains that meet the DCOF standard may have a rougher surface that might show dirt.
[3] Mosaic - Smallest mosaic size 3 x 3
[4] Alternate mortar - Ardex X5 White or Mapei Ultraflex LFT White
[5] Alternate grout - Mapei Ultracolor Plus FA or Ardex WA Epoxy
7.5% Recycled Content

Tech Notes: This material is made from 7.5% recycled content.