# LIMESTONE

The elegant simplicity of classic limestone is evoked by this 24”x 48” porcelain, offered in two colors; Cream and Sand. The semi-polished finish has a DCOF rating that makes this tile an ideal choice for floor installation in commercial spaces.

# LIMESTONE

*Sand*

*Cream*

## APPLICATIONS

| INTERIOR FLOOR | INTERIOR WALL | SHOWER WALL | SHOWER FLOOR | EXTERIOR FLOOR | EXTERIOR WALL | POOL/ FOUNTAIN | COUNTER TOP | FIREPLACE SURROUND |
|---|---|---|---|---|---|---|---|---|
| Light/ Medium Commercial | All | Yes, including steam | Yes, in mosaic formats only | No | Yes, including freeze thaw | Yes | Yes | Yes |

## ATTRIBUTES

| DCOF [1] |
|---|
| 0.52<br>0.53<br>0.55 |

## VARIATION




## INSTALLATION/MAINTENANCE

| SETTING MATERIAL | GROUT | GROUT JOINT | MEMBRANE | CAULK | SEALER | CLEANER | INSTALLATION INSTRUCTIONS | LAYOUT | DRY LAYOUT |
|---|---|---|---|---|---|---|---|---|---|
| Mapei Ultraflex LFT White [2] | Ardex FL Rapid Set Sanded [3] | 1/16" minimum | Ardex 8+9 | Ardex SX | AquaMix Grout Release | AquaMix Concentrated Cleaner | TCNA Handbook | 20.0% | Recommended |

## NOTES

[1] Porcelain Rectified field tile only
[2] Ardex X5 White Medium Bed Mortar
[3] Alternate grout - Mapei Ultracolor Plus FA or Mapei Flexcolor CQ
Tech Note: Per TCNA Guidlines, Running Bond/Brick Joint Patterns To Be Set With A Max. Offset Of 20% And Min. Grout Joint Of 1/16", Unless Otherwise Approved By Owner. Number of faces: 18

## AVAILABLE SIZES

RECTIFIED FIELD TILE
24" x 48" x 11/32"
*Semi-Polished*