NAMIB

Drawing inspiration from the Namib Desert, the Namib collection is a selection of rectified porcelain tiles that captures the depth and movement of majestic dunes in a sophisticated design. Rich in textural character, Namib Matte is a 24” x 24” tile with a uniform surface with intricate grain detailing and subtle color variations that reveal themselves upon closer inspection. Namib Texture, a 24” x 48” tile, offers a raked finish, adding a simple linear detail to the matte base. The Namib collection is available in Camel, Dune, Earth, Ecru, Jasper, and Linen.

NAMIB

Camel

Dune

Earth

Ecru

Jasper

Linen

APPLICATIONS

INTERIOR FLOOR	INTERIOR WALL	SHOWER WALL	SHOWER FLOOR	EXTERIOR FLOOR	EXTERIOR WALL	POOL/ FOUNTAIN	COUNTER TOP	FIREPLACE SURROUND
Commercial Light/Medium	All	Yes, including steam	Yes, including steam, linear drain	Yes, including freeze thaw	Yes, including freeze thaw	Yes	Yes	Yes

ATTRIBUTES

DCOF
0.74-0.71-0.73

VARIATION



INSTALLATION/MAINTENANCE

SETTING MATERIAL	GROUT	GROUT JOINT	MEMBRANE	CAULK	SEALER	CLEANER	INSTALLATION INSTRUCTIONS	LAYOUT	DRY LAYOUT	QR CODE
Ardex X77 White Microtec Fiber Reinforced Mortar[1]	Ardex FL Rapid Set Sanded [2,2]	1/16" minimum	Ardex 8 + 9	Ardex SX	AquaMix Grout Release	AquaMix Concentrated Cleaner	TCNA Handbook	Max. 33% Offset[3]	Recommended	

TAILORED TO CUSTOMIZATION

- CARPET CUTTING
- FIELD
- FINISH
- MOSAIC
- SADDLE
- VANITY TOP
- WATERJET

NOTES

[1] Alternate Mortar-Mapei Ultraflex LFT White or Ardex X5 White Medium Bed Mortar
[2] Alternate Grout-Mapei Ultracolor Plus FA or Ardex FG-C Microtec Unsanded
[3] Per TCNA Guidelines, running bond/brick joint patterns to be set with a max. offset of 33% and min. grout joint of 1/16".

Tech Notes: DCOF AcuTest - Porcelains that meet the DCOF standard may have a more abrasive surface that might show dirt or debris. Remove with soap, water and firm scrubbing in order to clean. Consider this in the selection process.

PORCELAIN FIELD TILE



24" x 24" x 3/8"
Porcelain Rectifed
FIELD TILE

NAMIB TEXTURED

Earth

Ecru

Linen

APPLICATIONS

INTERIOR FLOOR	INTERIOR WALL	SHOWER WALL	SHOWER FLOOR	EXTERIOR FLOOR	EXTERIOR WALL	POOL/ FOUNTAIN	COUNTER TOP	FIREPLACE SURROUND
No	All	Yes, including steam	No	No	Yes, including freeze thaw	Yes	No	Yes

VARIATION



INSTALLATION/MAINTENANCE

SETTING MATERIAL	GROUT	GROUT JOINT	MEMBRANE	CAULK	SEALER	CLEANER	INSTALLATION INSTRUCTIONS	LAYOUT	DRY LAYOUT	QR CODE
Ardex X77 White Microtec Fiber Reinforced Mortar[1]	Ardex FL Rapid Set Sanded [2]	1/16" minimum	Ardex 8 + 9	Ardex SX	AquaMix Grout Release	AquaMix Concentrated Cleaner	TCNA Handbook	Max. 33% Offset[3]	Recommended	

TAILORED TO CUSTOMIZATION

CARPET CUTTING
FIELD
FINISH
MOSAIC
SADDLE
VANITY TOP
WATERJET

NOTES

[1] Alternate Mortar-Ardex X5 White Medium Bed Mortar or Mapei Ultraflex LFT White
[2] Alternate Grout-Ardex FG-C Microtec Unsanded or Mapei Ultracolor Plus FA
[3] Per TCNA Guidelines, running bond/brick joint patterns to be set with a max. offset of 33% and min. grout joint of 1/16".

Tech Notes: Porcelains that meet the DCOF standard may have a more abrasive surface that might show dirt or debris. Remove with soap, water and firm scrubbing in order to clean. Consider this in the selection process. Per TCNA guidelines, running bond/brick joint patterns to be set with a max. offset of 33% and min. grout joint of 1/16", unless otherwise approved by owner. Grout release can be utilized, and bag grouting may be considered.

PORCELAIN FIELD TILE

24" x 48" x 3/8"
Porcelain Rectifed
FIELD TILE